

# **Fanless System**

# HBJC511F893-H310-B

Intel® 8th LGA 1151 Core i3 / i5 / i7 Processor, support DDR4 2133MHz up to 32GB

#### **Features**

- 1. Intel® 8th LGA 1151 Core i3 / i5 / i7 Processors (TDP 35W)
- 2. 2 \* SO-DIMM Dual CH DDR4 2133MHz up to 32GB
- 3. 4 \* USB2.0, 4 \* USB3.0, 2 \* COM, 1 \* DP, 1 \* HDMI, 1 \* RJ45, 1 \* MIC, 1 \* Line out
- 4. M/B Form Factor: Mini ITX (170x170mm)
- 5. DC19V/120W Adapter





## Front I/O



## Rear I/O





Model	CPU / Chipset
<ul> <li>HBJC511F893-H310B (Non-WiFi)</li> <li>HBJC511F893I-H310B (WiFi)</li> </ul>	<ul> <li>Intel® 8th LGA 1151 Socket Core i7 / i5 / i3 / Pentium / Celeron Processor (35W)</li> <li>Intel® H310 express chipset</li> </ul>
- UPIC211L0331-U310B (MILI)	Notes: When the system runs, CPU will automatically adjust its working clock frequency according to changing workload.
BIOS	Memory
AMI 128MB SMT Flash ROM	2 * 204-pin SO-DIMM slots supporting Dual CH DDR4 2666MHz up to 64GB
Network	Graphics
• 1 * Intel i219V GbE.	Intel® HD Graphics, shared memory
• 1 * M.2 E key(2230) slot for wifi	• 1* DP (Max Resolution: 4096x2304@60Hz
	• 2* HDMI 2.0 (Max Resolution: 4096x2160@60Hz)
	Support Triple Displays
Storage	Expansion
• 1* 2.5" SATAIII 6Gb/s internal drive bay (only support 2.5" HDD with a height ≤ 10mm)	1* PCle x1 slot
• 1* M.2 –M key (2242/2260/2280) slot	
Rear Panel I/O	Front Panel I/O
• 4* USB 3.0 ports	• 1 * Power button
<ul> <li>1 * HDMI 1.4 (Max. Resolution: 4096*2160@30Hz)</li> </ul>	• 1 * Reset button
• 1 * DP (Max. Resolution: 4096*2304@60Hz)	• 1 * Power LED
• 1 * RJ45	• 1 * HDD LED
• 1 * Line-out	• 2 * USB 2.0
• 1* MIC	• 1 * Line-out
2 * Antenna holes (WiFi only)	• 1 * MIC-in
• 1 * DC-in Jack	
Internal Connector	Power Source
1* LVDS / inverter (default, option with eDP)	• Adapter: AC100~240V_DC19V_120W
• 1* RS232	M/B: DC 19V input
Compliance	Dimensions

# CE, FCC, RoHS, ErP Ready Temperature

- $\bullet$  Operating Temperature: -20  $^{\sim}$  50° C (Under the condition of using M.2 interface SSD)
- $\bullet$  Operating Temperature: 0  $^{\sim}$  50° C (Under the condition of using 2.5" SATA HDD)

(The test environment is closed and windless)

- Storage Temperature: -20  $^{\sim}$  80° C
- Humidity: Between 40% and 60%, non-condensing

#### **OS Support**


Windows 10, Linux

#### Warranty


- 2 Years limited warranty
- \* Specifications subject to change without notice, not responsible for typographical errors. Does not include HDD or OS.

## Part Number Rules

System: 264 (W) x 199.4 (D) x 38 (H) mm



### Mechanical Drawings (Unit=mm)



## Ordering Info

Part Number	Description
HBJC511F893-H310B	HBJC511F893 series Barebone, Intel
	H310 express chipset CPU
HBJC511F893I-H310B	HBJC511F893 series Barebone, Intel
	H310 express chipset CPU, Wifi function
L01AS050-F	Adapter DC19V_120W
Change according to shipping area	Power cord
HCS5XXMWM01B-F	JC5XX Wall mount
LCSCHBJC3XX-F	Screw pack
HNSCOMWFCB375NF-F	WIFI-5 AC+BT5.0 AW-CB375NF M.2
	2230 (WIFI only)
J05-ANT-GX57245-F	Antenna 2G4/5G,
	2.8dBi GX572450001SM (WiFi only)
HCS3XXDINRAILPS-F	Din Rail Clip